



Fiberglass Lining
Plastic Coating
External Wrapping
Threading Services
Field Services
Pipe Services

AP BLACK

7812 West Hwy 80 • Midland, TX 79706 • 432.617.0242 • 432.617.0244 Fax

PRIMED AND COATED

Nylon based ID coating for tubing and casing in corrosive service.

FLEXIBILITY AND PERFORMANCE

Flexible molecular structure for continued protection in tension or compression.

TIGHT MOLECULAR CROSSLINK

Minimizes gas molecule penetration.
Performs well in CO₂ and water injection.

CONTINUOUS PROTECTION

Coated in coupling to protect the "J" area.



AP BLACK

ID Coating for Tubing and Casing

Product Information

TYPE	Nylon Powder with Primer
MAX TEMPERATURE	225° F
APPLIED THICKNESS	.010" to .020"
PRESSURE	Up to yield strength of the pipe
PRIMARY SERVICE	CO ₂ , SWD, Oil and Gas injection and production service
PRIMARY APPLICATION	Production tubing and casing
LIMITATIONS	Caution should be used in applications involving H ₂ S and stimulation acids above 15%

Nominal Dimensions

2 3/8 4.7		2 7/8 6.5		3 1/2 9.3		4 1/2 11.6	
Nominal Thickness	Nominal Drift	Nominal Thickness	Nominal Drift	Nominal Thickness	Nominal Drift	Nominal Thickness	Nominal Drift
.010"-.020"	1.866"	.010"-.020"	2.312"	.010"-.020"	2.832"	.010"-.020"	3.840"

Improved Flow Efficiency

AP Black internal plastic coating provides a smooth friction-reduced surface to increase the flowing efficiency of produced or injected gases and fluids.